



GIRJE LUBRICANT PVT. LTD.

Plot No.4, Market Committee, Narla Road, Paithan.
Dist. Aurangabad, State. Maharashtra (INDIA) - 431107.

Customer Care No. : +91 94234 55119

Email : info@girjelubricants.com

Website : www.girjelubricants.com

Bihar Regional Office : 2nd Floor, Veenadeep Bhawan,
In Front of Vyapar Mandal, Ward No -13, Kharaiya Basti, Araria,
Bihar - 854311

Contact : +91 88006 03002



**Protect Your
Engine Life**



OUR VISION & MISSION

Our mission is to develop best in class range of products that customers can use with confidence. In order to be the most trusted entity, we procure best grade chemical compounds and implement ultra-modern machineries to manage a quality approved product portfolio. Further, the competitive costs and assurance of timely deliveries made us capable to serve a huge client base. In addition, we follow the highest ethical standards to sustain our relationships with our stakeholders.

PRODUCT RANGE

BIKE ENGINE OIL

- 20W-40 API SN
- 20W-40 API SM
- 20W-40 API SL
- 10W-30 API SN

CAR ENGINE OIL

- 10W-40 API SL/CL
- 5W-30
- 20W-50 CNG
- ATF API TYPE - A

HEAVY DUTY ENGINE OIL

- 15W-40 API CF-4
- 15W-40 API CH-4
- 15W-40 API CI-4 / SN
- 20W-40 API CF-4
- 20W-40 API CD/SF (Pump Set)
- UTTO WET BRAKE

HYDRAULIC OIL

- HYDRAULIC 32
- HYDRAULIC 46
- HYDRAULIC 68

AUTOMOTIVE GREASE

- ALL PURPOSE GREASE (AP-3)
- MULTI PURPOSE GREASE (MP-3)
- CHASSIS GREASE
- RED GEL GREASE
- GOLDEN GEL GREASE

GEAR OIL

- SAE EP-90
- SAE 80W90
- SAE 85W140

OTHER OIL

- BRAKE OIL
- PREMIUM 2T (CNG OIL)
- FRONT FORK OIL
- COOLANT
- RPO (RUBBER PROCESSING OIL)

INDUSTRIAL OIL

- GEAR OIL 140 / 220 / 320
- HYDRAULIC OIL - 100
- STATE CUTTING OIL
- TRANSMISSION OIL
- LOOMS OIL



QUALITY ASSURANCE

Our quality policy is designed to abide us to the highest industrial standards. Our objectives to develop quality products that improve performance of LPG, petrol and diesel vehicles make us accountable to source premium quality raw materials. Further, we take special consideration to the formulation and purity standards of each product. Our team of trained quality analysts makes sure that each product undergoes a series of quality tests before dispatch.

WE PROVIDE QUALITY OF GOODS WHICH IS VERY HELPFUL TO GROWTH OF ENGINE LIFE.
WE ARE NATIONALIZED CERTIFIED COMPANY.



BIKE ENGINE OIL



20W-40 4T API SN / FASTER 4T Packing Size : 900ml, 1, 20, 55, 210 Ltr.



Girje Lubricant 4T Exceeds the most strengthen performance requirements of JASO MA2 and the value train wear requirements API SN Girje 4T is a premium quality 4-stroke engine oil specially formulated for high speed air-cooled engines of new generation motorcycles and scooter. The life boosting Oxy-Bioters in cleaner engine facilitates drain interval upto 5,000 kms Girje Lubricant 4T is recommended for use in the models of her motorcorp, Bajaj, Honda, TVS, Yamaha and all other manufacturer normal operating conditions.

20W-40 4T API SM Packing Size : 900ml, 1, 20, 55, 210 Ltr.



Girje Lubricant 4T Exceeds the most strengthen performance requirements of JASO MA2 and the value train wear requirements API SN Girje 4T is a premium quality 4-stroke engine oil specially formulated for high speed air-cooled engines of new generation motorcycles and scooter. The life boosting Oxy-Bioters in cleaner engine facilitates drain interval upto 4,000 kms Girje Lubricant 4T is recommended for use in the models of her motorcorp, Bajaj, Honda, TVS, Yamaha and all other manufacturer normal operating conditions.

20W-40 4T API SL / ACTION 4T Packing Size : 900ml, 1, 20, 55, 210 Ltr.



Girje Lubricant 4T Exceeds the most strengthen performance requirements of JASO MA2 and the value train wear requirements API SL Girje 4T is a premium quality 4-stroke engine oil specially formulated for high speed air-cooled engines of new generation motorcycles and scooter. The life boosting Oxy-Bioters in cleaner engine facilitates drain interval upto 3,000 kms Girje Lubricant 4T is recommended for use in the models of her motorcorp, Bajaj, Honda, TVS, Yamaha and all other manufacturer normal operating conditions.

10W-30 4T API SL Packing Size : 900ml, 20, 55, 210 Ltr.



Girje Lubricant 4T Exceeds the most strengthen performance requirements of JASO MA2 and the value train wear requirements API SN Girje 4T is a premium quality 4-stroke engine oil specially formulated for high speed air-cooled engines of new generation motorcycles and scooter. The life boosting Oxy-Bioters in cleaner engine facilitates drain interval upto 5,000 kms Girje Lubricant 4T is recommended for use in the models of her motorcorp, Bajaj, Honda, TVS, Yamaha and all other manufacturer normal operating conditions.

15W-50 BULLET ENGINE OIL Packing Size : 2.5, 3, 10, 20, 55, 210 Ltr.



GIRJE LUBRICANTS 15W-50 API SN Motor Oil is a high performance 4 stroke Motor Cycle Engine Oil. It is superior Multigrade detergent type lubricating oil meeting the highest API SN Performance level for petrol engines of new generation motor cycles, specially Royal Enfield. Excellent viscosity temperature characteristics. Low engine deposits. Extended drain intervals. Superior clutch friction performance. Excellent high temperature oxidation stability. Excellent sludge and varnish control. Excellent anti-wear properties

CAR ENGINE OIL

10W-40 API SL / CL Packing Size : 2.5, 3, 3.5, 4, 5, 10, 20, 55, 210 Ltr.



Girje 10w-40 API SL/CL is Suitable for use in both petrol and diesel engines. Offers excellent protection of engines components enhancing engine life. Specially formulated for enhanced engine performance. Recommended for use in all new generation petrol & diesel car made by Maruti, GeneralMotors/Chevrolet, Toyota, Ford Etc.

5W-30 (FORTUNE) Packing Size : 1, 2.5, 3, 3.5, 4, 5, 10, 20, 55, 210 Ltr.



Girje 5W-30 Fully Synthetic is Suitable for use in both petrol and diesel engines. Offers excellent protection of engines components enhancing engine life. Specially formulated for enhanced engine performance. Recommended for use in all new generation petrol & diesel car made by Maruti, GeneralMotors/Chevrolet, Toyota, Ford Etc.

20W-50 CNG Packing Size : 3, 3.5, 5, 10, 20, 55, 210 Ltr.



GIRJE LUBRICANTS CNG Engine oil is high performance engine oil for light vehicles operating on gas. Meets API SJ/CF as per specifications. Super Performance it terms of oxidation stability. Excellent wear protection at high temperature and serve operating conditions. Long engine oil. Catalytic Converter Compatible.

ATF API TYPE - A Packing Size : 500ml, 1, 5, 10, 20, 55, 210 Ltr.



GIRJE LUBRICANTS TQ is formulated to general motor's automatic transmission fluid type A suffix A specification. This fluid impart anti-oxidation, anti-wear, dispersancy, deforming and viscosity index and low pour point it assure quit and smooth operation of hydraulic equipment under all climatic condition. it is a fluid with low co-efficient of friction thus permitting clutch plates to engage slowly and gradually as the transmission shift. The fluid is compatible with seal material, generally used in transmission systems.

HEAVY DUTY ENGINE OIL



15W-40 API CF-4 Packing Size : 500ml, 1, 2.5, 3, 3.5, 4, 5, 7.5, 10, 20, 55, 210 Ltr.



GIRJE LUBRICANTS 15W-40 Engines oil meets the requirements of API CF-4. It is a heavy duty engine oil having high viscosity index. Offers excellent detergent inhibitions. Has good anti-wear anti-oxidant properties. GIRJE LUBRICANTS 15W-40 is recommended for all new generation engines.

15W-40 API CH-4 (TRACTOR) Packing Size : 500ml, 1, 2.5, 3, 3.5, 4, 5, 7.5, 10, 20, 55, 210 Ltr.



GIRJE LUBRICANTS 15W-40 is a diesel engine oil developed to meet the requirements of a variety naturally aspirated diesel engines operating under different conditions. It is protection to engines operating under various environments. It is suitable for use in a wide range of on and off-highway applications where such type of lubricant is recommended.

15W-40 API CH-4 (Extra Nitro) Packing Size : 500ml, 1, 2.5, 3, 3.5, 4, 5, 7.5, 10, 20, 55, 210 Ltr.



GIRJE LUBRICANTS 15W-40 engine oil meets the requirement of API CI-4. 15W40 is a heavy duty engine oil having high viscosity index. Offers excellent detergent inhibitions. It has good anti-wear and anti-oxidant properties. 15w40 Is recommended for all new generation engine.

20W-40 API CI-4 / SN (MOTOJET) Packing Size : 500ml, 1, 2.5, 3, 3.5, 4, 5, 7.5, 10, 20, 55, 210 Ltr.



GIRJE LUBRICANTS 15W-40 engine oil meets the requirement of API CI-4/SN. 15W40 is a heavy duty engine oil having high viscosity index. Offers excellent detergent inhibitions. It has good anti-wear and anti-oxidant properties. 15w40 Is recommended for all new generation engine.

20W-40 API CF-4 (TRACTOR) Packing Size : 1, 2.5, 3, 3.5, 4, 5, 7.5, 10, 20, 55, 210 Ltr.



GIRJE LUBRICANTS 20W-40 is a diesel engine oil developed to meet the requirements of a variety naturally aspirated diesel engines operating under different conditions. It is protection to engines operating under various environments. It is suitable for use in a wide range of on and off-highway applications where such type of lubricant is recommended.



HEAVY DUTY ENGINE OIL

- 20W-40 API CD/SF (Pump Set) Packing Size : 3, 3.5, 4, 5, 7.5, 10, 20, 55, 210 Ltr.



GIRJE LUBRICANTS is high performance multi grade engine oil for the lubrication of all kind of diesel/petrol pump sets used agricultural application. It is formulated to provide good wear protection and protect against rust, bearing corrosion and foaming

UTTO - WET ENGINE OIL Packing Size : 5, 10, 20, 55, 210 Ltr.



GIRJE Brakes Fluid is a heavy duty brake fluid processed from carefully selected ingredients and incorporates a balanced combination of anti-oxidants, metal deactivation and corrosion inhibitor. GIRJE Brakes Fluid is recommended for various we brake systems including disc type operating in various new generation automobiles.

HYDRAULIC OIL 32 / 46 / 68 Packing Size : 1, 5, 10, 20, 26, 55, 210 Ltr.



HYDRAULIC is a general purpose anti-wear hydraulic oil developed for use in a wide range of industrial hydraulic application, especially in less demanding applications where premium performance is required is formulated to provides good wear protection for hydraulic pumps and motors, good oxidation, resistance and protection against rust and corrosion, It has good water-separating properties to minimize the formulated of emissions and is resistant to excessive foam build up that can cause sluggish hydraulic system response.

GEAR OILS

EP-90 / API GL-4 GEAR OIL Packing Size : 500ml, 1, 5, 10, 20, 26, 55, 210 Ltr.



Gear oils are automotive extreme pressure multi-gear oils blended from specially selected high viscosity index base stocks and contain additives which import extreme pressure, anti-oxidation characteristics, this is multi-purpose type GIRJE Lubricant specifically formulated to meet the rigorous service demand of commercial fleet mechanical transmission, axles and gear boxes.

80W-90 / API GL-5 GEAR OIL Packing Size : 500ml, 1, 5, 10, 20, 26, 55, 210 Ltr.



GIRJE SAE 80W-90 Gear oil recommended premium high performance multigrade gear oil for hypoid gear differentials, mechanical transmissions of cars, light and heavy commercial vehicles. Meets SAE 80W-90 and API GL-5. Has Excellent chemical and thermal stability permitting use up to bulk oil temperature of 150°C.

GEAR OILS



85W-140 / API GL-5 GEAR OIL Packing Size : 1, 5, 10, 20, 26, 55, 210 Ltr.



Gear oils are automotive extreme pressure multi-gear oils blended from specially selected high viscosity index base stocks and contain additives which impart extreme pressure, anti-oxidation characteristics, this is multi-purpose type GIRJE Lubricant specifically formulated to meet the rigorous service demand of commercial fleet mechanical transmission, axles and gear boxes.

AUTOMOTIVE GREASE

AP-3 GREASE (LITHIUM GREASE) Packing Size : 250, 500 GM, 1, 5, 10, 18, 180 KG.



AP-3 Grease is functional greases, having extreme pressure (EP) properties. These grease possess excellent shear stability. High Load carrying properties & prevent welding & seizure of moving parts under shock loading condition. These greases are recommended for industrial & automotive, earth moving equipment. Gear couplings, electric motors, ball & roller bearings etc.

MP-3 GREASE (LITHIUM GREASE) Packing Size : 250, 500 GM, 1, 5, 10, 18, 180 KG.



MP-3 Grease is functional greases, having extreme pressure (EP) properties. These grease possess excellent shear stability. High Load carrying properties & prevent welding & seizure of moving parts under shock loading condition. These greases are Recommended for industrial & automotive, earth moving equipment. Gear couplings, electric motors, ball & roller bearings etc.

GOLDEN GEL GREASE (LITHIUM GREASE) Packing Size : 250, 500 GM, 1, 5, 10, 18, 180 KG.



GOLDEN GEL Grease is functional greases, having extreme pressure (EP) properties. These grease possess excellent shear stability. High Load carrying properties & prevent welding & seizure of moving parts under shock loading condition. These greases are recommended for industrial & automotive, earth moving equipment. Gear couplings, electric motors, ball & roller bearings etc.

CHASSIS GREASE (LITHIUM GREASE) Packing Size : 250, 500 GM, 1, 5, 10, 18, 180 KG.



CHASSIS Grease is functional greases, having extreme pressure (EP) properties. These grease possess excellent shear stability. High Load carrying properties & prevent welding & seizure of moving parts under shock loading condition. These greases are recommended for industrial & automotive, earth moving equipment. Gear couplings, electric motors, ball & roller bearings etc.



AUTOMOTIVE GREASE

RED GEL GREASE (LITHIUM GREASE) Packing Size : 250, 500 GM, 1, 5, 10, 18, 180 KG.



RED GEL Grease is functional greases, having extreme pressure (EP) properties. These grease possess excellent shear stability. High Load carrying properties & prevent welding & seizure of moving parts under shock loading condition. These greases are recommended for industrial & automotive, earth moving equipment. Gear couplings, electric motors, ball & roller bearings etc.

OTHER OILS

BRAKE OIL - DOT 3 / 4 / 5 Packing Size : 100, 250, 500 ML, 1, 5, 210 LTR.



BRAKE OIL Consistent and steady brake pressure response throughout service life, Optimal viscosity-even during extreme temperature conditions. Enhanced lubrication of the hydraulic components, Suitable for all hydraulic brake & clutch systems with the exception of those run on mineral oil.

FORK OIL - (SHOCKER OIL) Packing Size : 175, 350 ML, 210 LTR.



Girje Fork Oil is an advanced mineral based suspension fluid designed to provide superior damping performance in all on and off road suspensions.

COOLANT Packing Size : 1, 5, 10, 20, 55, 210 LTR.



Girje Ready to use coolant is a triple action long life radiator coolant prepared from selected ingredients to meet the highest Japanese standard and is free from Amines, Borates, Nitrates and Silicates.

PREMIUM 2T (CNG OIL) Packing Size : 500 ML, 1, 10, 20, 55, 210 LTR.



CNG 2T is superior product develops for two stroke petrol engines & are blended from highly refined base oils, additives & a diluent to provide easy mixing with fuel. these products minimize spark plug fouling & protection against scuffing, seizure & wear.

INDUSTRIAL OIL



ABOUT OUR COMPANY

GEAR OIL - 140 / 220 / 320

Packing Size : 10, 20, 26, 55, 210 LTR.



GEAR OIL is a premium quality Industrial and Automotive gear lubricant which recommended for enclosed industrial gears and heavily loaded plain or rolling-element bearings operating under extreme-temperature conditions. It is specially formulated to have a very high viscosity index for use over a wide range of operating temperatures.

HYDAULIC OIL - 100

Packing Size : 10, 20, 26, 55, 210 LTR.



Hydraulic series are premium quality lubricating oils intended for use in hydraulic systems in industrial service, circulating systems. These oils are blended from high quality base oils and additive system to provide superior oxidation stability, rust & corrosion protection, foam control and moderate wear protection.

STATE CUTTING OIL

Packing Size : 10, 20, 26, 55, 210 LTR.



STATE CUTTING OIL Suitable for all metals for machining operations where emulsifiable oil are normally used. The recommended concentration is between 5 to 10 % depending on the severity of machining. Sometimes used successfully for even grinding operations.

TRANSMISSION OIL

Packing Size : 10, 20, 26, 55, 210 LTR.



TRANSMISSION OIL is a high quality automatic transmission fluid manufactured from highly refined base stocks and carefully selected additives, to provide a superior performance in the automatic transmission systems of automotive.

LOOMS OIL

Packing Size : 10, 20, 26, 55, 210 LTR.



LOOMS OIL These all are formulated for mineral oils having good adhesion and film strength, inherent oxidation and thermal stability, besides excellent ability to separate from water resistant to rusting and corrosion

QUALITY ASSURANCE

We have facility to produce advance work various industrial applications based on specially developed technology are also ready.

INFRASTRUCTURE

We are authoritative in manufacturing the qualitative products and our well integrated work set up is our key to growth. Our infrastructure is scattered over a large area and features adequate expansion potential.

EFFECTIVE TEAM WORK

For, GIRJE LUBRICANT, commitment of its employees is a critical resource. Fully realizing that only a satisfied and motivated employee will put his best foot forward with the customers, GIRJE LUBRICANT has taken many steps to make the organization a 'Great Place to Work'.

GIRJE LUBRICANT has been certified for Quality Management System (ISO 9001:2015).

